

# TECHNICAL BULLETIN

**Kemiko Rocky Mountain**  
dba The Ader Image  
5326 Tennyson St  
Denver, CO 80212  
Phone: (303) 286-8111  
Fax: (303) 286-8113  
Web: [www.kemiko-rockymtn.com](http://www.kemiko-rockymtn.com) • E-Mail: [info@kemiko-rockymtn.com](mailto:info@kemiko-rockymtn.com)

## **EASY STRIP** *Heavy Duty – Water Base Wax Stripper*

### Description

**EASY STRIP** is a high performance water base wax stripper designed specifically for removing *Kemiko Stone Tone* and *Easy Shine* waxes. EASY STRIP is water viscosity, single component product with a slight ammonia odor that does not contain any hazardous solvents, is concentrated, can be diluted with water, and easily removes wax build up.

### Applications

**EASY STRIP** is typically applied to concrete substrates, which have received *Kemiko Stone Tone Stain*, and topcoated with *Kemiko Stone Tone Sealer II*, *Kemiko Epoxy*, & *Kemiko Polyurethane*, followed by selected wax product. EASY STRIP is applied with commercially available low-pressure sprayers or simply poured onto floor and worked into the surface with a stiff bristle brush, pads, or floor machine. Typical applications include domestic and commercial kitchens, grocery stores, restaurants, showroom floors, walkways, and many other interior and exterior surfaces requiring removal of wax build up.

### Performance

- ✓ **INDUSTRIAL STRENGTH** – *Can be reduced 100%-200% with water*
- ✓ **VERSATILE** – *Removes waxes, dirt, grease, and grime, vegetable oils.*
- ✓ **ENVIRONMENTALLY SAFE** – *Biodegradable.*

### Physical Characteristics

Component:	Ammonia/Alkaline Concentrate in Water
Packaging:	1s, 5s, 55s
FlashPoint:	None
Shelf Life:	6-months
Odor:	Slight Ammonia
Storage Temperature:	40-100°F.
Appearance:	Clear
Coverage:	200-500 square feet per gallon – per application
Reduction:	Light Duty – 1-part Easy Strip to 2 parts Water Medium Duty – 1-part Easy Strip to 1 part Water Heavy Duty – Apply Easy Strip without dilution

### Surface Preparation

**BARE CONCRETE** – Use Easy Strip to remove wax build, visible oil, grease, sludge, stain residue and any other contaminants that cosmetically affect re-waxing the substrate. Apply Easy Strip to substrate, allow 2-3 minutes to “wet in” then scrub using stiff bristle brooms, brushes or heavy duty floor scrubbing machines. DO NOT ALLOW EASY STRIP TO DRY ON SURFACE. Once the scrubbing action is completed, rinse surface with clean fresh water and vacuum. Check surface again to insure all wax and any other deleterious matter is removed. Repeat application of Easy Strip if necessary. Surface shall be allowed to dry thoroughly prior to any re-waxing application.

**EXISTING COATINGS/SEALERS** – Apply small amount of Easy Strip on surface, allow to stand 2-3 minutes and rinse with fresh water. If existing coating or sealer is not affected (removed) by Easy Strip, proceed as instructed above for surface preparation. ACRYLIC SEALERS MAY BE COMPROMISED OR DESTROYED WITH EASY STRIP. APPLY EASY STRIP DILUTED 1X-2X WITH WATER ON ACRYLIC OR REMBRANDT STAINED FLOORS. Make sure to check compatibility prior to application.

### Application Methods

**Brush** – Use top-quality nylon bristle brush for application in corners or hard to reach areas.

**Floor Machine** – Electrical rotary type utilizing soft pads or white scouring pads for heavy duty cleaning and wax removal.

**Spray** – Low pressure “Hudson” type commercial sprayers to apply product followed by scrubbing action.

**Environment** – Apply between 50°F. – 100°F. and 5°F. above dewpoint. Do not store in direct sunlight. Protect from freezing. Do not apply to wet or frosted surfaces.

**Warning – eye and skin irritation.** HARMFUL IF SWALLOWED. Avoid eye and skin contact. Wear latex or rubber gloves. Wash skin thoroughly after handling. Remove any clothing that has been in contact with this material and wash thoroughly. **First Aid:** Eye contact: Flush immediately with plenty of clear water for 15 minutes then seek medical attention. Skin contact: Wash with soap and water. If an irritation results, seek medical attention. If swallowed, do not induce vomiting. Seek medical attention. Do not reuse container. Refer to MSDS for further information. **KEEP OUT OF REACH OF CHILDREN**

### WARRANTY

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product, which is proved to be defective. Any claim of defective product must be received in writing within one (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss, or damage resulting from use of this product.  
4/16/2007